



# Ecofix New

## Chemical description

Product based on ester of fatty acid in emulsion

## Main use

Medium for decals application

## Typical values

---

Appearance at 20 °C: Dense green emulsion

---

Viscosity (Brookfield RVT @ 20°C, 20 rpm): 10000 – 20000 cPs

---

## Product properties

ECOFIX NEW is an intermediary which allows the application of decals (decoration, logo, bar code,..) onto any type of ceramic raw glazes.

## Applications

ECOFIX NEW is applied by spray gun or by brush. To obtain an excellent result we recommend application of a uniform and thin layer. ECOFIX NEW is normally diluted 50 : 50 or 60 : 40 in water, but it can also be used alone when necessary.

## Storage and handling

ECOFIX NEW is stable to prolonged storage under condition where extreme temperatures do not occur. the shelf life is at least twelve months if this condition is observed. Store between 20 - 40°C.

A partial separation of the product components is possible after a long period of storage, but the product becomes homogeneous again after thorough stirring.

## Packaging

20 Kg – 50 kg plastic drum

## Material safety

Consult the Safety Data Sheet

[ceramics.lamberti.com](http://ceramics.lamberti.com)

This information and our technical recommendations, if any, both verbal and in writing, are given to the best of our knowledge, without any express or implied warranty, e.g., regarding their fitness for a specific purpose. Each user of our products is the sole responsible for assessing and ensuring compliance with all legal regulations including intellectual property laws and necessary certifications and authorizations with respect to the use, combination and processing of our products. Our technical recommendations do not release the user from the obligation to check its validity and to test our products as to their suitability and fitness for the intended processes and uses. The application, use and processing of both our products and the products manufactured by the user (on the basis of our technical recommendations, if any) are beyond our control and, therefore, the user is the sole responsible for them. Detailed information and instructions on handling the products and cautions to be observed in the use of them are available in our relevant Safety Data Sheet.