



# Gritmed 0840

## Chemical description

Synthetic polymers in water solution

## Main use

Fixative for grits

## Typical values

Appearance at 20 °C:	liquid
Colour:	Red
pH (1% dispersion):	8 ± 1
Density (g/l) :	1020 ± 10

## Product properties

GRITMED 0840 is a binder used for the application of glaze granulates or grits on the surface of the tile.

It's a water based binder "Ready to use" that can apply on the tiles, sprayed by gun/airless

The binding part of the product allows the grits to be anchored homogeneously, obtaining a perfectly spread surface.

## Applications

GRITMED 0840 can be spray alone or mixed with variable amount of liquid glaze.

Usually it's recommended the following ratio:

<b>Involved materials</b>	<b>Application ratio</b>
Gritmed/glaze	80 ÷ 20

## Storage and handling

GRITMED 0840 when stored under normal conditions of temperature (5°C to 40°C) is stable and maintains its characteristics for at least 12 month.

[ceramics.lamberti.com](http://ceramics.lamberti.com)

This information and our technical recommendations, if any, both verbal and in writing, are given to the best of our knowledge, without any express or implied warranty, e.g., regarding their fitness for a specific purpose. Each user of our products is the sole responsible for assessing and ensuring compliance with all legal regulations including intellectual property laws and necessary certifications and authorizations with respect to the use, combination and processing of our products. Our technical recommendations do not release the user from the obligation to check its validity and to test our products as to their suitability and fitness for the intended processes and uses. The application, use and processing of both our products and the products manufactured by the user (on the basis of our technical recommendations, if any) are beyond our control and, therefore, the user is the sole responsible for them. Detailed information and instructions on handling the products and cautions to be observed in the use of them are available in our relevant Safety Data Sheet.