



Printojet S LV 0338

Chemical Description

Mixture of organic polymers

Main Use

Liquid additive for Inkjet digital glaze

Typical use

Appearance at 20 °C: Liquid

Colour: Opalescent yellowish

Density (g/l): 1060

Solubility in water: Complete at every ratios

Product Properties

Printojet S LV 0338 is a liquid additive, with low viscosity, specially designed for the preparation of the digital glazes. The effectiveness of Printojet S LV 0338 is due to its high dispersing power, lubricant and binder properties. Added to the glaze or solid engobe, Printojet S LV 0338 guarantees an excellent stability, avoiding settling effect and improving the surface quality.

Due to its rheological properties Printojet S LV 0338 is suitable for glazes and engobes with high clay content.

Applications

Glaze or Engobe / Printojet S LV 0338	100 (powder) / 3 - 5 %
---------------------------------------	------------------------

Dosage

For specific application of glaze follow the rheological parameters and particle size released by the installer.

Storage and Handling

Printojet S LV 0338 if stored correctly it is stable 12 months.

The product should be stored at temperatures between -5°C and 40°C.

Packaging

Tanks 1000 kg ; Plastic drums 125 Kg

Material Safety

"Detailed health and safety information can be found in our safety data sheet, available according to ECC Directive".