



Viscolam

Chemical Description

Synthetic/Natural polymers

Main Use

Rheological modifier

Typical Values

Appearance at 25 °C: Liquid

Product Properties

VISCOLAM are concentrated thickeners, used for increasing the viscosity of printing pastes, either for colours or white thick applications. They must be added to the pastes during mechanical stirring, and they keep a constant rheology during the application and the storage.

Applications

Paste / Viscolam	100 / 1 - 3
------------------	-------------

Storage and Handling

When stored in an original unopened packaging, not under direct sun rays, between 5 and +40 ° the product has a shelf life of 6 months from the date of manufacture.

However, it is advisable to shake it before use.

Packaging

IBC and drums

Material Safety

Consult the Safety Data Sheet

ceramics.lamberti.com

This information and our technical recommendations, if any, both verbal and in writing, are given to the best of our knowledge, without any express or implied warranty, e.g., regarding their fitness for a specific purpose. Each user of our products is the sole responsible for assessing and ensuring compliance with all legal regulations including intellectual property laws and necessary certifications and authorizations with respect to the use, combination and processing of our products. Our technical recommendations do not release the user from the obligation to check its validity and to test our products as to their suitability and fitness for the intended processes and uses. The application, use and processing of both our products and the products manufactured by the user (on the basis of our technical recommendations, if any) are beyond our control and, therefore, the user is the sole responsible for them. Detailed information and instructions on handling the products and cautions to be observed in the use of them are available in our relevant Safety Data Sheet.